

Rackmount Telemetry Transmitter Platform



Easy Does It

With integrated cooling, a browser interface, a new API, and more, our Rackmount Transmitter Platform simplifies deployment and operation of your telemetry transmitters. Quasonix is... Reinventing Telemetry™.

Rackmount Enclosure – Rugged 2U rackmount chassis provides a single box accommodating up to four (4) 2" x 3" or two (2) 4" x 3" transmitters (sold separately).

Flexible Transmitter Options – Choose up to four (4) single output transmitters or up to two (2) dual output transmitters.

Browser-Based GUI – Easy-to-use, intuitive web interface, using any ordinary browser to control the transmitters. Detailed logging includes history of changes made to the transmitters.

NEW! Applications Programming Interface (API) – Provides powerful access to status and control of the transmitters by a client computer.

Strong Administrative Functions – Manage transmitter names, user privileges, clock settings, IP address, and system.

Field Upgradable Software – Update to the latest software from the client browser.

Master RF On/Off – Ability to enable/disable RF on all channels via a secure locking toggle switch.

Exceptional Cooling – Internal heat sinks and fans provide the cooling power to keep transmitters operating at peak performance.

High Quality Connectors – Uses the same BNCs and N connectors found on our rackmount receivers.

Available 85 VAC to 264 VAC, 50/60 Hz or 120 to 370 VDC Operation – Specify AC or DC operation.



Rackmount Transmitter Specifications

Inputs / Outputs

Connectors—RF Output	Up to four (4) N female connectors
Clock and Data	TTL (BNC) or RS-422 (Isolated BNC)
Ethernet	Ruggedized RJ-45
Power	85 VAC to 264 VAC, 50/60 Hz or 120 to 370 VDC


Active inputs and outputs depend on configuration ordered.

Physical

Dimensions	2U rackmount chassis; 18.95" W, 3.45" H, 13.83 rack depth, 14.00" overall depth
------------	---

Environmental

Operating Temperature	0°C to +50°C
Storage Temperature	0°C to +70°C
Operating Humidity	0 to 95% (non-condensing)
Altitude	Up to 30,000 ft.


Server Time: 2022-10-11 18:51:26

Slot 1
Home Tx Detail Settings Terminal Logs About

Slot 1-- Transmitter 1 (S/N: 14728)

Connection			Settings			Status		RF Power			
Slot ID	Display Name	Connected	Mode	Frequency	Power	BB Clock (Mbps)	Temperature	Command	Switch	BB Clk Ok	RF Actual
1	Transmitter 1	True	PCMFEM	2200.5	31.5	5.000010	36.07	<input type="checkbox"/>	1	1	On
2	Transmitter 2	True	SOQPSK	2225.5	31.5	4.999994	38.32	<input type="checkbox"/>	1	1	On
3	Transmitter 3	True	SOQPSK	2250.5	31.5	4.999994	38.05	<input type="checkbox"/>	1	1	On
4	Transmitter 4	True	SOQPSK	2275.5	31.5	4.999994	37.03	<input type="checkbox"/>	1	1	On

© Copyright 2022 by Quasonix, Inc.

Browser-based GUI facilitates monitoring status and controlling up to four transmitters at one time.



All Quasonix products are under U.S. Dept. of Commerce jurisdiction. Transmitter products are categorized as EAR99.
ISO 9001:2015 Certified | Specifications subject to change without notice.

6025 Schumacher Park Drive West Chester, OH 45069 | 1-513-942-1287 | www.quasonix.com