

TRANSMITTER PINOUT CODE N7

Connector: Female 21-pin Nano



| Pin | Function | | |
|-----|-----------------------------|--|--|
| 1 | Serial Control Ground | | |
| 2 | RS-232 Serial Control Reply | | |
| 3 | RS-232 Serial Control Input | | |
| 4 | Dual Power | | |
| 5 | N/C | | |
| 6 | Differential Data Positive | | |
| 7 | Differential Clock Positive | | |
| 8 | DC Power Return | | |
| 9 | RF On/Off | | |
| 10 | DC Power Return | | |
| 11 | DC Power Return | | |
| 12 | DC Power Return | | |
| 13 | DC Power In | | |
| 14 | DC Power In | | |
| 15 | DC Power In | | |
| 16 | N/C | | |
| 17 | N/C | | |
| 18 | N/C | | |
| 19 | N/C | | |
| 20 | Differential Data Negative | | |
| 21 | Differential Clock Negative | | |

No part of the document may be circulated, quoted, or reproduced for distribution without prior written approval from Quasonix, Inc.



| DRAWING | qsx_pcn7.docx | | |
|----------|---------------|------|------------|
| REVISION | В | | |
| DRAWN | MRE | DATE | 08-22-2018 |
| VERIFIED | DEF | DATE | 08-22-2018 |
| APPROVED | DEF | DATE | 08-22-2018 |